

1 Introduction

L^AT_EX looks more difficult than it is. It is almost as easy as π . See how easy it is to make special symbols such as α , β , γ , δ , $\sin x$, \hbar , λ , \dots . We also can make subscripts A_x , A_{xy} and superscripts, e^x , e^{x^2} , and e^{ab} . We will use L^AT_EX, which is based on T_EX and has many higher-level commands (macros) for formatting, making tables, etc. More information can be found in Ref. [1].

We just made a new paragraph. Extra lines and spaces make no difference. Note that all formulas are enclosed by $\$$ and occur in *math mode*.

The default font is Computer Modern. It includes *italics*, **boldface**, *slanted*, and monospaced fonts.

2 Equations

Let us see how easy it is to write equations.

$$\Delta = \sum_{i=1}^N w_i (x_i - \bar{x})^2. \quad (1)$$

It is a good idea to number equations, but we can have a equation without a number by writing

$$P(x) = \frac{x - a}{b - a},$$

and

$$g = \frac{1}{2} \sqrt{2\pi}.$$

We can give an equation a label so that we can refer to it later.

$$E = -J \sum_{i=1}^N s_i s_{i+1}, \quad (2)$$

Equation (2) expresses the energy of a configuration of spins in the Ising model.¹

We can define our own macros to save typing. For example, suppose that we introduce the macros:

```
\newcommand{\lb}{\langle}
\newcommand{\rb}{\rangle}
```

Then we can write the average value of x as

```
\begin{equation}
\lb x \rb = 3
\end{equation}
```

The result is

$$\langle x \rangle = 3. \tag{3}$$

Examples of more complicated equations:

$$I = \int_{-\infty}^{\infty} f(x) dx. \tag{4}$$

We can do some fine tuning by adding small amounts of horizontal spacing:

```
\, small space      \! negative space
```

as is done in Eq. (4).

We also can align several equations:

$$a = b \tag{5}$$

$$c = d, \tag{6}$$

or number them as subequations:

$$a = b \tag{7a}$$

$$c = d. \tag{7b}$$

We can also have different cases:

$$m(T) = \begin{cases} 0 & T > T_c \\ (1 - [\sinh 2\beta J]^{-4})^{1/8} & T < T_c \end{cases} \tag{8}$$

¹It is necessary to process (typeset) a file twice to get the counters correct.

write matrices

$$\begin{aligned} \mathbf{T} &= \begin{pmatrix} T_{++} & T_{+-} \\ T_{-+} & T_{--} \end{pmatrix}, \\ &= \begin{pmatrix} e^{\beta(J+B)} & e^{-\beta J} \\ e^{-\beta J} & e^{\beta(J-B)} \end{pmatrix}. \end{aligned} \tag{9}$$

and

$$\sum_i \vec{A} \cdot \vec{B} = -P \int \mathbf{r} \cdot \hat{\mathbf{n}} dA = P \int \vec{\nabla} \cdot \mathbf{r} dV. \tag{10}$$

3 Tables

Tables are a little more difficult. TeX automatically calculates the width of the columns.

lattice	d	q	T_{mf}/T_c
square	2	4	1.763
triangular	2	6	1.648
diamond	3	4	1.479
simple cubic	3	6	1.330
bcc	3	8	1.260
fcc	3	12	1.225

Table 1: Comparison of the mean-field predictions for the critical temperature of the Ising model with exact results and the best known estimates for different spatial dimensions d and lattice symmetries.

4 Lists

Some example of formatted lists:

1. bread
 2. cheese
- Tom
 - Dick

5 Figures

We can make figures bigger or smaller by scaling them. Figure 2 has been scaled by 60%.




Figure 1: Show me a sine.




Figure 2: Plot of the Lennard-Jones potential $u(r)$. The potential is characterized by a length σ and an energy ϵ .

6 Literal text

It is desirable to print program code exactly as it is typed in a monospaced font. Use `\begin{verbatim}` and `\end{verbatim}` as in the following example:

```
double y0 = 10; // example of declaration and assignment statement
double v0 = 0; // initial velocity
double t = 0; // time
double dt = 0.01; // time step
double y = y0;
```

The command `\verbatiminput{programs/Square.java}` allows you to list the file `Square.java` in the directory `programs`.

7 Special Symbols

7.1 Common Greek letters

These commands may be used only in math mode. Only the most common letters are included here.

$\alpha, \beta, \gamma, \Gamma, \delta, \Delta, \epsilon, \zeta, \eta, \theta, \Theta, \kappa, \lambda, \Lambda, \mu, \nu, \xi, \Xi, \pi, \Pi, \rho, \sigma, \tau, \phi, \Phi, \chi, \psi, \Psi, \omega, \Omega$

7.2 Special symbols

The derivative is defined as

$$\frac{dy}{dx} = \lim_{\Delta x \rightarrow 0} \frac{\Delta y}{\Delta x} \quad (11)$$

$$f(x) \rightarrow y \quad \text{as} \quad x \rightarrow x_0 \quad (12)$$

$$f(x) \xrightarrow{x \rightarrow x_0} y \quad (13)$$

Order of magnitude:

$$\log_{10} f \simeq n \quad (14)$$

$$f(x) \sim 10^n \quad (15)$$

Approximate equality:

$$f(x) \simeq g(x) \quad (16)$$

L^AT_EX is simple if we keep everything in proportion:

$$f(x) \propto x^3. \tag{17}$$

Finally we can skip some space by using commands such as

```
\bigskip \medskip \smallskip \vspace{1pc}
```

The space can be negative.

8 Use of Color

We can change colors for emphasis, but who is going pay for the ink?

9 Subfigures

As soon as many students start becoming comfortable using L^AT_EX, they want to use some of its advanced features. So we now show how to place two figures side by side.




Figure 3: Two representations of complex wave functions.

We first have to include the necessary package, `\usepackage{subfigure}`, which has to go in the preamble (before `\begin{document}`). It sometimes can be difficult to place a figure in the desired place.

Your LaTeX document can be easily modified to make a poster or a screen presentation similar to (and better than) PowerPoint. Conversion to HTML is straightforward. Comments on this tutorial are appreciated.

References

- [1] Helmut Kopka and Patrick W. Daly, *A Guide to L^AT_EX: Document Preparation for Beginners and Advanced Users*, fourth edition, Addison-Wesley (2004).
- [2] Some useful links are given at `<http://sip.clarku.edu/tutorials/TeX/>`.

Updated 5 December 2006.